


*A printer small enough to fit into
whatever little space you have*



Optional accessories



Dispenser



Label Cutter

CT400/410
Plug & Play Barcode Printer

CT400/410

- Space Saving & Compact
- High Speed
- Easy creation of Label Format with Windows Program
- Easy Media Loading
- Casing Made of Inorganic Antimicrobial, High Heat-resistant Material

CT400/410

General Specifications:



Print Method	Thermal Transfer, Direct Thermal
Print Resolution	CT400: 203 dpi (8dpmm) CT410: 305 dpi (12dpmm)
Max. Print Area	W 104mm x L 381mm (W 4.1" x 15.0")
Print Speed	CT400: 152mm/sec (6"/sec) CT410: 102mm/sec (4"/sec)
Media Size	Width: 25mm - 118mm (1.0" - 4.6") Length: 15mm - 400mm (0.6" - 15.7")
Ribbon	Width: Up to 111mm (4.4") Length: Up to 100m (328ft) Wind: Face-Out
Sensor Type	Movable Transmissive Sensor for Die-Cut Labels Reflective Sensor for use with Pre-printed eye-mark Automatic or Programmable setting of top of form
Processor	32 - Bit RISC, 80 MHz
Interface Choices	Standard Parallel: IEEE 1284 Optional Serial: RS-232C, Ready / Busy X-on/X-off LAN USB: Version 1.1
Barcode Symbologies	UPC-A/E; EAN-8/13; Code 39, 93 & 128; Interleaved 2 of 5; Matrix 2 of 5; Codabar MSI; Bookland; POSTNET; UCC/EAN-128; PDF 417; Maxicode; Data Matrix
Barcode Ratio	1:2; 1:3; 1:2.5; or individually adjustable bar width
Matrix Fonts	12 Proportional & Mono-Spaced Fonts including Fonts OCR-A & OCR-B; Outline Font Amercian & European Characters; Upper & Lower case with Descenders
Functions	Sequential Numbering of both numerics and barcodes RAM Storage for special characters Full dot addressable graphics, SATO Hex/ Binary and PCX Formats Form Overlay for high-speed editing of complete formats
Dimension	W 198mm x D 230mm x H 181mm (W 7.8" x D 9.06" x H 7.13"); 3kg (6.61 lb)
Power Requirements	100 - 120 / 200 - 240V (+/-10%); 14.5VDC (+/-5V), 3.6A(Peak 13A); 50/60 Hz (+/-1%) Operating :150W or less
Environment	Operating: 41 ~ 104°F (5 ~ 40°C) non-condensing; Humidity: 15 - 85% RH Storage 0 ~ 104°F (-20 ~ 40°C) non condensing; Humidity: Max 90% RH
Regulatory Approvals	UL; CSA; CE; TUV
Options	Label Cutter; Label Dispenser; Linerless Media Kit

VOSUNG 铎盛科技
WWW.VOSUNG.COM